

Technical Specifications

Model	PGL 203	PGL 303	PGL 2002	PGL 3002	PGL 4001	PGL 6001	PGL 8001	PGL 10001	PGL 20001
Maximum capacity	200g	300g	2000g	3000g	4000g	6000g	8000g	10kg	20kg
Readability	0.001g	0.001g	0.01g	0.01g	0.1g	0.1g	0.1g	0.1g	0.1g
Repeatability (S.D.)	0.002g	0.003g	0.02g	0.03g	0.2g	0.2g	0.2g	0.2g	0.2g
Linearity (±)	0.004g	0.006g	0.04g	0.06g	0.2g	0.2g	0.2g	0.4g	0.4g
Pan size	145×125mm		192×192mm					400×300mm	
Net weight	4kg							6kg	

General Specifications

Typical stabilisation time	2-3 Sec
Units of measurement	Gram (g), Kilogram (kg), Milligram (mg), Carat (ct), Pound (lb), Ounce (Oz), Pound-Ounce (lb-oz), Grain (GN), Troy Ounce (Ozt), Pennyweight (dWt), Newton (N), Custom unit
Operating temperature	0°C 40°C
Power supply	12VDC 800mA AC adaptor and rechargeable battery pack
Calibration	Automatic External
Display	Backlit LCD display with dual digits and capacity tracker
Overall dimensions (wxdxh)	251×358×104mm
Dimensions notes	400 x 460 x 100mm (PGL10001 & PGL20001)

Key Accessories

- Density Determination Kit (mg models only)
- RS-232 to USB Interface Cable (must be ordered with 3074010266 RS232 cable)
- Security Lock and Cable
- Anti-Vibration Table
- Below Balance Hanger
- In-use Cover
- Dust Cover
- Adam Printer
- AdamDU - Data Collection Program
- RS-232 Cable
- Thermal Paper Roll for Adam Printer



新發興機械(馬)有限公司
Sin Huat Hin Machinery (M) Sdn. Bhd.

241232-A

Since 1968

<http://www.shhmach.com>

Email: sinhuathin@shhmach.com

HEAD OFFICE, SHOWROOM, & WORKSHOP

No. 697, Taman Chip Aik, Jalan Tun Dr. Ismail, 70200 Seremban, NSDK, Malaysia.
TEL: +(6) 06 763 3388, +(6) 06 765 3339 FAX: +(6) 06 762 8188, +(6) 06 765 3334

KUALA LUMPUR BRANCH OFFICE

No. B1-00-20, Jalan SR 1/9, Taman Serdang Raya, Sri Kembangan,
43300 Serdang Raya, Selangor, Malaysia.

TEL : +(6) 03 8942 5711, +(6) 03 8945 2202 FAX: +(6) 03 8948 3151